



900 Series

Tilting bratt pans 900

GAS TILTING BRATT PAN, SBG9-10

DIMENSIONS

| | | <u>Article</u> | <u>Packed</u> |
|---------|----|----------------|-----------------|
| Length | mm | 850,00 | 910,00 |
| Depth | mm | 900,00 | 1.060,00 |
| Height | mm | 850,00 | 1.085,00 |
| Weigth | Kg | 195,00 | 218,00 |
| Volumen | m3 | 0,65 | 1,05 |

ELECTRICITY

| <u>Electric power</u> | | KW | |
|-----------------------|--|----|----------------------|
| 230V -1+N | | | 0,05 |
| 230V - III | | | 2x1,5+T - 2 A |
| 400V - III+N | | | |

WATER

Not used

GAS

| | | | |
|-------------|--|--------------------|------------------|
| Power | | KW | 18,60 |
| | | Kcal/h | 15.996,00 |
| LPG | | Consumption (kg/h) | 1,32 |
| | | Pressure (g/cm2) | 37,00 |
| Natural Gas | | Consumption (m3/h) | 1,78 |
| | | Pressure (g/cm2) | 18,00 |

STEAM

Not used

AIR

Not used

GAS TILTING BRATT PAN, SBG9-10

Made of stainless steel

Pan capacity: 80 litres (approx.). Surface area: 50 dm2

Cast iron pan, with crank raising system.

Counterweighted folding lid.

Stainless steel tubular burner controlled by solenoid valve and thermostat temperature control (50 °C to 315 °C).

Water filling tap.


Power: 16000 kcal/h. (18.6 kW).

Dimensions: 850 x 900 x 850 mm.

Certificate EQNET- CE

99AP57

| <u>Connections points</u> | <u>X</u> | <u>Y</u> | <u>Z</u> | <u>Diameter</u> | <u>Information</u> |
|---------------------------|----------|----------|----------|-----------------|--|
| ELECTRICITY | 600 | 764 | 150 | | Prever Interruptor diferencial |
| COLD WATER | 805 | 575 | 105 | 1/2" | Prever llave de corte en la toma |
| GAS | 805 | 635 | 105 | R.3/4"G | Prever regulador y llave de corte individual |





900 Series

Tilting bratt pans 900

GAS TILTING BRATT PAN, SBG9-10 S

DIMENSIONS

| | | Article | Packed |
|---------|----|---------|----------|
| Length | mm | 850,00 | 900,00 |
| Depth | mm | 900,00 | 1.050,00 |
| Height | mm | 700,00 | 1.080,00 |
| Weigth | Kg | 195,00 | 218,00 |
| Volumen | m3 | 0,54 | 1,02 |

ELECTRICITY

| Electric power | KW | |
|----------------|----|---------------|
| 230V -1+N | | 0,05 |
| 230V - III | | 2x1,5+T - 2 A |
| 400V - III+N | | |

WATER

Not used

GAS

| | | |
|-------------|--------------------|-----------|
| Power | KW | 18,60 |
| | Kcal/h | 15.996,00 |
| LPG | Consumption (kg/h) | 1,32 |
| | Pressure (g/cm2) | 37,00 |
| Natural Gas | Consumption (m3/h) | 1,78 |
| | Pressure (g/cm2) | 18,00 |

STEAM

Not used

AIR

Not used

GAS TILTING BRATT PAN, SBG9-10 S

Made of stainless steel

Pan capacity: 80 litres (approx.).

Surface area: 50 dm2

Cast iron pan, with crank raising system.

Counterweighted folding lid.

Stainless steel tubular burner controlled by solenoid valve and thermostat temperature control (50 °C to 315 °C).

Water filling tap.


Power: 16000 kcal/h. (18.6 kW).

Dimensions: 850 x 900 x 620 mm.

Certificate EQNET- CE

99AP57

| Connections points | X | Y | Z | Diameter | Information |
|--------------------|-----|-----|---|----------|--|
| ELECTRICITY | 675 | 125 | 0 | | Prever Interruptor diferencial |
| COLD WATER | 630 | 80 | 0 | 1/2" | Prever llave de corte en la toma |
| GAS | 675 | 80 | 0 | R.3/4"G | Prever regulador y llave de corte individual |





900 Series

Tilting bratt pans 900

GAS TILTING BRATT PAN, SBG9-10 I

DIMENSIONS

| | | <u>Article</u> | <u>Packed</u> |
|---------|----|----------------|-----------------|
| Length | mm | 850,00 | 910,00 |
| Depth | mm | 900,00 | 1.060,00 |
| Height | mm | 850,00 | 1.085,00 |
| Weigth | Kg | 172,00 | 195,00 |
| Volumen | m3 | 0,65 | 1,05 |

ELECTRICITY

| <u>Electric power</u> | | KW | |
|-----------------------|--|----|----------------------|
| 230V -1+N | | | 0,05 |
| 230V - III | | | 2x1,5+T - 2 A |
| 400V - III+N | | | |

WATER

Not used

GAS

| | | | |
|-------------|--------------------|--------|------------------|
| Power | | KW | 18,60 |
| | | Kcal/h | 15.996,00 |
| LPG | Consumption (kg/h) | | 1,32 |
| | Pressure (g/cm2) | | 37,00 |
| Natural Gas | Consumption (m3/h) | | 1,78 |
| | Pressure (g/cm2) | | 18,00 |

STEAM

Not used

AIR

Not used

GAS TILTING BRATT PAN, SBG9-10 I

Made of stainless steel

Pan capacity: 80 litres (approx.). Surface area: 50 dm2

Stainless steel pan, with heat diffuser bottom 10 mm. thick. Crank raising system. Counterweighted folding lid.

Stainless steel tubular burner controlled by solenoid valve and thermostat temperature control (50 °C to 315 °C).

Water filling tap.


Power: 16000 kcal/h. (18.6 kW).

Dimensions: 850 x 900 x 850 mm.

Certificate EQNET- CE

99AP57

| Connections points | X | Y | Z | Diameter | Information |
|---------------------------|----------|----------|----------|-----------------|--|
| ELECTRICITY | 600 | 764 | 150 | | Prever Interruptor diferencial |
| COLD WATER | 805 | 575 | 105 | 1/2" | Prever llave de corte en la toma |
| GAS | 805 | 635 | 105 | R.3/4"G | Prever regulador y llave de corte individual |





900 Series

Tilting bratt pans 900

GAS TILTING BRATT PAN, SBG9-10 I S

DIMENSIONS

| | | <u>Article</u> | <u>Packed</u> |
|---------|----|----------------|-----------------|
| Length | mm | 850,00 | 900,00 |
| Depth | mm | 900,00 | 1.050,00 |
| Height | mm | 700,00 | 1.080,00 |
| Weigth | Kg | 171,00 | 194,00 |
| Volumen | m3 | 0,54 | 1,02 |

ELECTRICITY

| <u>Electric power</u> | | KW | |
|-----------------------|--|----|----------------------|
| 230V -1+N | | | 0,05 |
| 230V - III | | | 2x1,5+T - 2 A |
| 400V - III+N | | | |

WATER

Not used

GAS

| Power | | KW | |
|-------------|--------------------|--------------|------------------|
| | | 18,60 | |
| | | | 15.996,00 |
| LPG | Consumption (kg/h) | | 1,32 |
| | Pressure (g/cm2) | | 37,00 |
| Natural Gas | Consumption (m3/h) | | 1,78 |
| | Pressure (g/cm2) | | 18,00 |

STEAM

Not used

AIR

Not used

GAS TILTING BRATT PAN, SBG9-10 I S

Made of stainless steel

Pan capacity: 80 litres (approx.). Surface area: 50 dm2

Stainless steel pan, with heat diffuser bottom 10 mm. thick. Crank raising system. Counterweighted folding lid.

Stainless steel tubular burner controlled by solenoid valve and thermostat temperature control (50 °C to 315 °C).

Water filling tap.


Power: 16000 kcal/h. (18.6 kW).

Dimensions: 850 x 900 x 620 mm.

Certificate EQNET- CE

99AP57

| Connections points | X | Y | Z | Diameter | Information |
|--------------------|-----|-----|---|----------|--|
| ELECTRICITY | 675 | 125 | 0 | | Prever Interruptor diferencial |
| COLD WATER | 630 | 80 | 0 | 1/2" | Prever llave de corte en la toma |
| GAS | 675 | 80 | 0 | R.3/4"G | Prever regulador y llave de corte individual |





900 Series

Tilting bratt pans 900

GAS TILTING BRATT PAN, SBG9-10 M

DIMENSIONS

| | | Article | Packed |
|---------|----|---------|----------|
| Length | mm | 850,00 | 910,00 |
| Depth | mm | 900,00 | 1.060,00 |
| Height | mm | 850,00 | 1.085,00 |
| Weigth | Kg | 195,00 | 218,00 |
| Volumen | m3 | 0,65 | 1,05 |

ELECTRICITY

| Electric power | KW | |
|----------------|----|---------------|
| 230V -1+N | | 2x1,5+T - 2 A |
| 230V - III | | |
| 400V - III+N | | |

WATER

Not used

GAS

| | | |
|-------------|--------------------|-----------|
| Power | KW | 18,60 |
| | Kcal/h | 15.996,00 |
| LPG | Consumption (kg/h) | 1,32 |
| | Pressure (g/cm2) | 37,00 |
| Natural Gas | Consumption (m3/h) | 1,78 |
| | Pressure (g/cm2) | 18,00 |

STEAM

Not used

AIR

Not used

GAS TILTING BRATT PAN, SBG9-10 M

Made of stainless steel

Pan capacity: 80 litres (approx.). Surface area: 50 dm2

Cast iron pan, with automatic tilt system.

Counterweighted folding lid.

Stainless steel tubular burner controlled by solenoid valve and thermostat temperature control (50 °C to 315 °C).

Water filling tap.


Power: 16000 kcal/h. (18.6 kW).

Dimensions: 850 x 900 x 850 mm.

Certificate EQNET- CE

99AP57

| Connections points | X | Y | Z | Diameter | Information |
|--------------------|-----|-----|-----|----------|--|
| ELECTRICITY | 600 | 764 | 150 | | Prever Interruptor diferencial |
| COLD WATER | 805 | 575 | 105 | 1/2" | Prever llave de corte en la toma |
| GAS | 805 | 635 | 105 | R.3/4"G | Prever regulador y llave de corte individual |





900 Series

Tilting bratt pans 900

GAS TILTING BRATT PAN, SBG9-10 M S

DIMENSIONS

| | | <u>Article</u> | <u>Packed</u> |
|---------|----|----------------|-----------------|
| Length | mm | 850,00 | 900,00 |
| Depth | mm | 900,00 | 1.050,00 |
| Height | mm | 700,00 | 1.080,00 |
| Weigth | Kg | 195,00 | 218,00 |
| Volumen | m3 | 0,54 | 1,02 |

ELECTRICITY

| <u>Electric power</u> | | KW | |
|-----------------------|--|----|----------------------|
| 230V -1+N | | | 0,06 |
| 230V - III | | | 2x1,5+T - 2 A |
| 400V - III+N | | | |

WATER

Not used

GAS

| | | | |
|-------------|--|--------------------|------------------|
| Power | | KW | 18,60 |
| | | Kcal/h | 15.996,00 |
| LPG | | Consumption (kg/h) | 1,32 |
| | | Pressure (g/cm2) | 37,00 |
| Natural Gas | | Consumption (m3/h) | 1,78 |
| | | Pressure (g/cm2) | 18,00 |

STEAM

Not used

AIR

Not used

GAS TILTING BRATT PAN, SBG9-10 M S

Made of stainless steel

Pan capacity: 80 litres (approx.). Surface area: 50 dm2

Cast iron pan, with automatic tilt system.

Counterweighted folding lid.

Stainless steel tubular burner controlled by solenoid valve and thermostat temperature control (50 °C to 315 °C).

Water filling tap.


Power: 16000 kcal/h. (18.6 kW).

Dimensions: 850 x 900 x 750 mm.

Certificate EQNET- CE

99AP57

| <u>Connections points</u> | <u>X</u> | <u>Y</u> | <u>Z</u> | <u>Diameter</u> | <u>Information</u> |
|---------------------------|----------|----------|----------|-----------------|--|
| ELECTRICITY | 675 | 125 | 0 | | Prever Interruptor diferencial |
| COLD WATER | 630 | 80 | 0 | 1/2" | Prever llave de corte en la toma |
| GAS | 675 | 80 | 0 | R.3/4"G | Prever regulador y llave de corte individual |





900 Series

Tilting bratt pans 900

GAS TILTING BRATT PAN, SBG9-10 IM

DIMENSIONS

| | | <u>Article</u> | <u>Packed</u> |
|---------|----|----------------|-----------------|
| Length | mm | 850,00 | 910,00 |
| Depth | mm | 900,00 | 1.060,00 |
| Height | mm | 850,00 | 1.085,00 |
| Weigth | Kg | 172,00 | 195,00 |
| Volumen | m3 | 0,65 | 1,05 |

ELECTRICITY

| <u>Electric power</u> | | KW | |
|-----------------------|--|----|----------------------|
| 230V -1+N | | | 0,06 |
| 230V - III | | | 2x1,5+T - 2 A |
| 400V - III+N | | | |

WATER

Not used

GAS

| | | | |
|-------------|--------------------|--------|------------------|
| Power | | KW | 18,60 |
| | | Kcal/h | 15.996,00 |
| LPG | Consumption (kg/h) | | 1,32 |
| | Pressure (g/cm2) | | 37,00 |
| Natural Gas | Consumption (m3/h) | | 1,78 |
| | Pressure (g/cm2) | | 18,00 |

STEAM

Not used

AIR

Not used

GAS TILTING BRATT PAN, SBG9-10 IM

Made of stainless steel

Pan capacity: 80 litres (approx.). Surface area: 50 dm2

Stainless steel pan, with heat diffuser bottom 10 mm. thick. Automatic tilt system. Counterweighted folding lid.

Stainless steel tubular burner controlled by solenoid valve and thermostat temperature control (50 °C to 315 °C).

Water filling tap.


Power: 16000 kcal/h. (18.6 kW).

Dimensions: 850 x 900 x 850 mm.

Certificate EQNET- CE

99AP57

| Connections points | X | Y | Z | Diameter | Information |
|---------------------------|----------|----------|----------|-----------------|--|
| ELECTRICITY | 600 | 764 | 150 | | Prever Interruptor diferencial |
| COLD WATER | 805 | 575 | 105 | 1/2" | Prever llave de corte en la toma |
| GAS | 805 | 635 | 105 | R.3/4"G | Prever regulador y llave de corte individual |





900 Series

Tilting bratt pans 900

GAS TILTING BRATT PAN, SBG9-10 IMS

DIMENSIONS

| | | <u>Article</u> | <u>Packed</u> |
|---------|----|----------------|-----------------|
| Length | mm | 850,00 | 900,00 |
| Depth | mm | 900,00 | 1.050,00 |
| Height | mm | 700,00 | 1.080,00 |
| Weigth | Kg | 171,00 | 194,00 |
| Volumen | m3 | 0,54 | 1,02 |

ELECTRICITY

| <u>Electric power</u> | | KW | |
|-----------------------|--|----|----------------------|
| 230V -1+N | | | 0,06 |
| 230V - III | | | 2x1,5+T - 2 A |
| 400V - III+N | | | |

WATER

Not used

GAS

| | | | |
|-------------|--|--------------------|------------------|
| Power | | KW | 18,60 |
| | | Kcal/h | 15.996,00 |
| LPG | | Consumption (kg/h) | 1,32 |
| | | Pressure (g/cm2) | 37,00 |
| Natural Gas | | Consumption (m3/h) | 1,78 |
| | | Pressure (g/cm2) | 18,00 |

STEAM

Not used

AIR

Not used

GAS TILTING BRATT PAN, SBG9-10 I M S

Made of stainless steel

Pan capacity: 80 litres (approx.). Surface area: 50 dm2

Stainless steel pan, with heat diffuser bottom 10 mm. thick. Automatic tilt system. Counterweighted folding lid.

Stainless steel tubular burner controlled by solenoid valve and thermostat temperature control (50 °C to 315 °C).

Water filling tap.


Power: 16000 kcal/h. (18.6 kW).

Dimensions: 850 x 900 x 750 mm.

Certificate EQNET- CE

99AP57

| Connections points | X | Y | Z | Diameter | Information |
|---------------------------|----------|----------|----------|-----------------|--|
| ELECTRICITY | 675 | 125 | 0 | | Prever Interruptor diferencial |
| COLD WATER | 630 | 80 | 0 | 1/2" | Prever llave de corte en la toma |
| GAS | 675 | 80 | 0 | R.3/4"G | Prever regulador y llave de corte individual |





900 Series

Tilting bratt pans 900

GAS TILTING BRATT PAN, SBG9-15 IM

DIMENSIONS

| | | <u>Article</u> | <u>Packed</u> |
|---------|----|-----------------|-----------------|
| Length | mm | 1.275,00 | 1.330,00 |
| Depth | mm | 900,00 | 1.110,00 |
| Height | mm | 850,00 | 1.135,00 |
| Weigth | Kg | 228,00 | 269,00 |
| Volumen | m3 | 0,98 | 1,68 |

ELECTRICITY

| <u>Electric power</u> | | KW | |
|-----------------------|--|----|----------------------|
| 230V -1+N | | | 0,06 |
| 230V - III | | | 2x1,5+T - 2 A |
| 400V - III+N | | | |

WATER

Not used

GAS

| | | | |
|-------------|--|--------------------|------------------|
| Power | | KW | 26,70 |
| | | Kcal/h | 22.962,00 |
| LPG | | Consumption (kg/h) | 2,09 |
| | | Pressure (g/cm2) | 37,00 |
| Natural Gas | | Consumption (m3/h) | 2,65 |
| | | Pressure (g/cm2) | 18,00 |

STEAM

Not used

AIR

Not used

GAS TILTING BRATT PAN, SBG9-15 IM

Made of stainless steel

Pan capacity: 120 litres (approx.). Surface area: 75 dm2

Stainless steel pan, with heat diffuser bottom 10 mm. thick. Automatic tilt system. Counterweighted folding lid.

Stainless steel tubular burner controlled by solenoid valve and thermostat temperature control (50 °C to 315 °C).

Water filling tap.


Power: 23000 kcal. (26.7 kW).

Dimensions: 1275 x 900 x 850 mm.

Certificate EQNET- CE

99AP57

| <u>Connections points</u> | <u>X</u> | <u>Y</u> | <u>Z</u> | <u>Diameter</u> | <u>Information</u> |
|---------------------------|----------|----------|----------|-----------------|--|
| ELECTRICITY | 1.025 | 764 | 150 | | Prever Interruptor diferencial |
| COLD WATER | 1.230 | 575 | 105 | 1/2" | Prever llave de corte en la toma |
| GAS | 1.230 | 635 | 105 | R.3/4"G | Prever regulador y llave de corte individual |





900 Series

Tilting bratt pans 900

GAS TILTING BRATT PAN, SBG9-15 IMS

DIMENSIONS

| | | <u>Article</u> | <u>Packed</u> |
|---------|----|-----------------|-----------------|
| Length | mm | 1.275,00 | 1.330,00 |
| Depth | mm | 900,00 | 1.110,00 |
| Height | mm | 700,00 | 1.090,00 |
| Weigth | Kg | 228,00 | 269,00 |
| Volumen | m3 | 0,80 | 1,61 |

ELECTRICITY

| <u>Electric power</u> | | KW | |
|-----------------------|--|----|----------------------|
| 230V -1+N | | | 0,06 |
| 230V - III | | | 2x1,5+T - 2 A |
| 400V - III+N | | | |

WATER

Not used

GAS

| | | | |
|-------------|--|--------------------|------------------|
| Power | | KW | 26,70 |
| | | Kcal/h | 22.962,00 |
| LPG | | Consumption (kg/h) | 2,09 |
| | | Pressure (g/cm2) | 37,00 |
| Natural Gas | | Consumption (m3/h) | 2,65 |
| | | Pressure (g/cm2) | 18,00 |

STEAM

Not used

AIR

Not used

GAS TILTING BRATT PAN, SBG9-15 I M S

Made of stainless steel

Pan capacity: 120 litres (approx.). Surface area: 75 dm2

Stainless steel pan, with heat diffuser bottom 10 mm. thick. Automatic tilt system. Counterweighted folding lid.

Stainless steel tubular burner controlled by solenoid valve and thermostat temperature control (50 °C to 315 °C).

Water filling tap.


Power: 23000 kcal. (26.7 kW).

Dimensions: 1275 x 900 x 750 mm

Certificate EQNET- CE

99AP57

| <u>Connections points</u> | <u>X</u> | <u>Y</u> | <u>Z</u> | <u>Diameter</u> | <u>Information</u> |
|---------------------------|----------|----------|----------|-----------------|--|
| ELECTRICITY | 1.085 | 182 | 0 | | Prever Interruptor diferencial |
| COLD WATER | 1.045 | 80 | 0 | 1/2" | Prever llave de corte en la toma |
| GAS | 1.085 | 80 | 0 | R.3/4"G | Prever regulador y llave de corte individual |





900 Series

Tilting bratt pans 900

ELECTRIC TILTING BRATT PAN, SBE9-10

DIMENSIONS

| | | <u>Article</u> | <u>Packed</u> |
|---------|----|----------------|-----------------|
| Length | mm | 850,00 | 910,00 |
| Depth | mm | 900,00 | 1.060,00 |
| Height | mm | 850,00 | 1.085,00 |
| Weigth | Kg | 195,00 | 218,00 |
| Volumen | m3 | 0,65 | 1,05 |

ELECTRICITY

| <u>Electric power</u> | KW | |
|-----------------------|----|-----------------------|
| 230V -1+N | | 12,00 |
| 230V - III | | 2x10+T - 63 A |
| 400V - III+N | | 3x6+T - 40 A |
| | | 4x2,5+T - 20 A |

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC TILTING BRATT PAN, SBE9-10

Made of stainless steel

Pan capacity: 80 litres (approx.). Surface area: 50 dm²

Cast iron pan, with crank raising system.

Counterweighted folding lid.

Shielded elements controlled by thermostat. Pilot lights.


Thermostat temperature control (50 °C to 315 °C).

Water filling tap.

Power: 12000 W.

Dimensions: 850 x 900 x 850 mm.

| Connections points | X | Y | Z | Diameter | Information |
|---------------------------|----------|----------|----------|-----------------|----------------------------------|
| ELECTRICITY | 600 | 764 | 150 | | Prever Interruptor diferencial |
| COLD WATER | 805 | 575 | 105 | 1/2" | Prever llave de corte en la toma |





900 Series

Tilting bratt pans 900

ELECTRIC TILTING BRATT PAN, SBE9-10 S

DIMENSIONS

| | | <u>Article</u> | <u>Packed</u> |
|---------|----|----------------|-----------------|
| Length | mm | 850,00 | 910,00 |
| Depth | mm | 900,00 | 1.060,00 |
| Height | mm | 700,00 | 1.085,00 |
| Weigth | Kg | 195,00 | 218,00 |
| Volumen | m3 | 0,54 | 1,05 |

ELECTRICITY

| <u>Electric power</u> | KW | |
|-----------------------|----|-----------------------|
| 230V -1+N | | 12,00 |
| 230V - III | | 2x10+T - 63 A |
| 400V - III+N | | 3x6+T - 40 A |
| | | 4x2,5+T - 20 A |

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC TILTING BRATT PAN, SBE9-10 S

Made of stainless steel

Pan capacity: 80 litres (approx.). Surface area: 50 dm²

Cast iron pan, with crank raising system.

Counterweighted folding lid.

Shielded elements controlled by thermostat. Pilot lights.


Thermostat temperature control (50 °C to 315 °C).

Water filling tap.

Power: 12000 W.

Dimensions: 850 x 900 x 620 mm

| Connections points | X | Y | Z | Diameter | Information |
|---------------------------|----------|----------|----------|-----------------|----------------------------------|
| ELECTRICITY | 675 | 125 | 0 | | Prever Interruptor diferencial |
| COLD WATER | 630 | 80 | 0 | 1/2" | Prever llave de corte en la toma |





900 Series

Tilting bratt pans 900

ELECTRIC TILTING BRATT PAN, SBE9-10 M

DIMENSIONS

| | | <u>Article</u> | <u>Packed</u> |
|---------|----|----------------|-----------------|
| Length | mm | 850,00 | 910,00 |
| Depth | mm | 900,00 | 1.060,00 |
| Height | mm | 850,00 | 1.085,00 |
| Weigth | Kg | 195,00 | 218,00 |
| Volumen | m3 | 0,65 | 1,05 |

ELECTRICITY

| <u>Electric power</u> | KW | |
|-----------------------|----|-----------------------|
| 230V -1+N | | 12,00 |
| 230V - III | | 2x10+T - 63 A |
| 400V - III+N | | 3x6+T - 40 A |
| | | 4x2,5+T - 20 A |

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC TILTING BRATT PAN, SBE9-10 M

Made of stainless steel

Pan capacity: 80 litres (approx.). Surface area: 50 dm²

Cast iron pan, with automatic tilting system.

Counterweighted folding lid.

Shielded elements controlled by thermostat. Pilot lights.


Thermostat temperature control (50 °C to 315 °C).

Water filling tap.

Power: 12000 W.

Dimensions: 850 x 900 x 850 mm.

| Connections points | X | Y | Z | Diameter | Information |
|---------------------------|----------|----------|----------|-----------------|----------------------------------|
| ELECTRICITY | 600 | 764 | 150 | | Prever Interruptor diferencial |
| COLD WATER | 805 | 575 | 105 | 1/2" | Prever llave de corte en la toma |





900 Series

Tilting bratt pans 900

ELECTRIC TILTING BRATT PAN, SBE9-10 MS

DIMENSIONS

| | | Article | Packed |
|---------|----|---------|----------|
| Length | mm | 850,00 | 910,00 |
| Depth | mm | 900,00 | 1.060,00 |
| Height | mm | 700,00 | 1.085,00 |
| Weigth | Kg | 195,00 | 218,00 |
| Volumen | m3 | 0,54 | 1,05 |

ELECTRICITY

| Electric power | KW | |
|----------------|----|----------------|
| 230V -1+N | | 2x10+T - 63 A |
| 230V - III | | 3x6+T - 40 A |
| 400V - III+N | | 4x2,5+T - 20 A |

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC TILTING BRATT PAN, SBE9-10 MS

Made of stainless steel

Pan capacity: 80 litres (approx.). Surface area: 50 dm²

Cast iron pan, with automatic tilting system.

Counterweighted folding lid.

Shielded elements controlled by thermostat. Pilot lights.


Thermostat temperature control (50 °C to 315 °C).

Water filling tap.

Power: 12000 W.

Dimensions: 850 x 900 x 620 mm.

| Connections points | X | Y | Z | Diameter | Information |
|--------------------|-----|-----|---|----------|----------------------------------|
| ELECTRICITY | 675 | 125 | 0 | | Prever Interruptor diferencial |
| COLD WATER | 630 | 80 | 0 | 1/2" | Prever llave de corte en la toma |





900 Series

Tilting bratt pans 900

ELECTRIC TILTING BRATT PAN, SBE9-10 I

DIMENSIONS

| | | <u>Article</u> | <u>Packed</u> |
|---------|----|----------------|-----------------|
| Length | mm | 850,00 | 910,00 |
| Depth | mm | 900,00 | 1.060,00 |
| Height | mm | 850,00 | 1.085,00 |
| Weigth | Kg | 172,00 | 195,00 |
| Volumen | m3 | 0,65 | 1,05 |

ELECTRICITY

| <u>Electric power</u> | KW | |
|-----------------------|----|-----------------------|
| 230V -1+N | | 2x10+T - 63 A |
| 230V - III | | 3x6+T - 40 A |
| 400V - III+N | | 4x2,5+T - 20 A |

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC TILTING BRATT PAN, SBE9-10 I

Made of stainless steel

Pan capacity: 80 litres (approx.). Surface area: 50 dm²

Stainless steel pan, with heat diffuser bottom 10 mm. thick

Crank raising system . Counterweighted folding lid.

Shielded elements controlled by thermostat. Pilot lights.


Thermostat temperature control (50 °C to 315 °C).

Water filling tap.

Power: 12000 W.

Dimensions: 850 x 900 x 850 mm.

| Connections points | X | Y | Z | Diameter | Information |
|---------------------------|----------|----------|----------|-----------------|----------------------------------|
| ELECTRICITY | 600 | 764 | 150 | | Prever Interruptor diferencial |
| COLD WATER | 805 | 575 | 105 | 1/2" | Prever llave de corte en la toma |





900 Series

Tilting bratt pans 900

ELECTRIC TILTING BRATT PAN, SBE9-10 IS

DIMENSIONS

| | | Article | Packed |
|---------|----|---------|----------|
| Length | mm | 850,00 | 910,00 |
| Depth | mm | 900,00 | 1.060,00 |
| Height | mm | 700,00 | 1.085,00 |
| Weigth | Kg | 171,00 | 195,00 |
| Volumen | m3 | 0,54 | 1,05 |

ELECTRICITY

| Electric power | KW | |
|----------------|----|----------------|
| 230V -1+N | | 2x10+T - 63 A |
| 230V - III | | 3x6+T - 40 A |
| 400V - III+N | | 4x2,5+T - 20 A |

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC TILTING BRATT PAN, SBE9-10 IS

Made of stainless steel

Pan capacity: 80 litres (approx.). Surface area: 50 dm²

Stainless steel pan, with heat diffuser bottom 10 mm. thick Crank raising system . Counterweighted folding lid.

Shielded elements controlled by thermostat. Pilot lights.


Thermostat temperature control (50 °C to 315 °C).

Water filling tap.

Power: 12000 W.

Dimensions: 850 x 900 x 620 mm.

| Connections points | X | Y | Z | Diameter | Information |
|--------------------|-----|-----|---|----------|----------------------------------|
| ELECTRICITY | 675 | 125 | 0 | | Prever Interruptor diferencial |
| COLD WATER | 630 | 80 | 0 | 1/2" | Prever llave de corte en la toma |





900 Series

Tilting bratt pans 900

ELECTRIC TILTING BRATT PAN, SBE9-10 IM

DIMENSIONS

| | | <u>Article</u> | <u>Packed</u> |
|---------|----|----------------|---------------|
| Length | mm | 850,00 | 910,00 |
| Depth | mm | 900,00 | 1.060,00 |
| Height | mm | 850,00 | 1.085,00 |
| Weigth | Kg | 172,00 | 195,00 |
| Volumen | m3 | 0,65 | 1,05 |

ELECTRICITY

| <u>Electric power</u> | KW | |
|-----------------------|----|----------------|
| 230V -1+N | | 2x10+T - 63 A |
| 230V - III | | 3x6+T - 40 A |
| 400V - III+N | | 4x2,5+T - 20 A |

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC TILTING BRATT PAN, SBE9-10 IM

Made of stainless steel

Pan capacity: 80 litres (approx.). Surface area: 50 dm²

Stainless steel pan, with heat diffuser bottom 10 mm. thick. Automatic tilt system. Counterweighted folding lid.

Shielded elements controlled by thermostat. Pilot lights.


Thermostat temperature control (50 °C to 315 °C).

Water filling tap.

Power: 12000 W.

Dimensions: 850 x 900 x 850 mm.

| <u>Connections points</u> | <u>X</u> | <u>Y</u> | <u>Z</u> | <u>Diameter</u> | <u>Information</u> |
|---------------------------|----------|----------|----------|-----------------|----------------------------------|
| ELECTRICITY | 600 | 764 | 150 | | Prever Interruptor diferencial |
| COLD WATER | 805 | 575 | 105 | 1/2" | Prever llave de corte en la toma |





900 Series

Tilting bratt pans 900

ELECTRIC TILTING BRATT PAN, SBE9-10 IMS

DIMENSIONS

| | | Article | Packed |
|---------|----|---------|----------|
| Length | mm | 850,00 | 910,00 |
| Depth | mm | 900,00 | 1.060,00 |
| Height | mm | 700,00 | 1.085,00 |
| Weigth | Kg | 171,00 | 194,00 |
| Volumen | m3 | 0,54 | 1,05 |

ELECTRICITY

| Electric power | KW | |
|----------------|----|----------------|
| 230V -1+N | | 2x10+T - 63 A |
| 230V - III | | 3x6+T - 40 A |
| 400V - III+N | | 4x2,5+T - 20 A |

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC TILTING BRATT PAN,
SBE9-10 I M S

Made of stainless steel

Pan capacity: 80 litres (approx.). Surface area: 50 dm²

Stainless steel pan, with heat diffuser bottom 10 mm. thick. Automatic tilt system. Counterweighted folding lid.

Shielded elements controlled by thermostat. Pilot lights.


Thermostat temperature control (50 °C to 315 °C).

Water filling tap.

Power: 12000 W.

Dimensions: 850 x 900 x 620 mm.

| Connections points | X | Y | Z | Diameter | Information |
|--------------------|-----|-----|---|----------|----------------------------------|
| ELECTRICITY | 675 | 125 | 0 | | Prever Interruptor diferencial |
| COLD WATER | 630 | 80 | 0 | 1/2" | Prever llave de corte en la toma |





900 Series

Tilting bratt pans 900

ELECTRIC TILTING BRATT PAN, SBE9-15 IM

DIMENSIONS

| | | Article | Packed |
|---------|----|----------|----------|
| Length | mm | 1.275,00 | 910,00 |
| Depth | mm | 900,00 | 1.060,00 |
| Height | mm | 850,00 | 1.085,00 |
| Weigth | Kg | 228,00 | 269,00 |
| Volumen | m3 | 0,98 | 1,05 |

ELECTRICITY

| Electric power | KW | |
|----------------|----|----------------|
| 230V - 1+N | | 2x16+T - 100 A |
| 230V - III | | 3x10+T - 63 A |
| 400V - III+N | | 4x4+T - 32 A |

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC TILTING BRATT PAN, SBE9-15 IM

Made of stainless steel

Pan capacity: 120 litres (approx.). Surface area: 75 dm²

Stainless steel pan, with heat diffuser bottom 10 mm. thick. Automatic tilt system. Counterweighted folding lid.

Shielded elements controlled by thermostat. Pilot lights.


Thermostat temperature control (50 °C to 315 °C).

Water filling tap.

Power: 18000 W.

Dimensions: 1275 x 900 x 850 mm.

| Connections points | X | Y | Z | Diameter | Information |
|--------------------|-------|-----|-----|----------|----------------------------------|
| ELECTRICITY | 1.025 | 764 | 150 | | Prever Interruptor diferencial |
| COLD WATER | 1.230 | 575 | 105 | 1/2" | Prever llave de corte en la toma |





900 Series

Tilting bratt pans 900

**ELECTRIC TILTING BRATT PAN, SBE9-15
IMS**

DIMENSIONS

| | | <u>Article</u> | <u>Packed</u> |
|---------|----|-----------------|-----------------|
| Length | mm | 1.275,00 | 910,00 |
| Depth | mm | 900,00 | 1.060,00 |
| Height | mm | 700,00 | 1.085,00 |
| Weigth | Kg | 228,00 | 269,00 |
| Volumen | m3 | 0,80 | 1,05 |

ELECTRICITY

| <u>Electric power</u> | KW | |
|-----------------------|----|-----------------------|
| 230V -1+N | | 18,00 |
| 230V - III | | 2x16+T - 100 A |
| 400V - III+N | | 3x10+T - 63 A |
| | | 4x4+T - 32 A |

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC TILTING BRATT PAN,
SBE9-15 I M S

Made of stainless steel

Pan capacity: 120 litres (approx.). Surface area: 75 dm²

Stainless steel pan, with heat diffuser bottom 10 mm. thick. Automatic tilt system. Counterweighted folding lid.

Shielded elements controlled by thermostat. Pilot lights.

Thermostat temperature control (50 °C to 315 °C).

Water filling tap.

Power: 18000 W.

Dimensions: 1275 x 900 x 750 mm.

| <u>Connections points</u> | <u>X</u> | <u>Y</u> | <u>Z</u> | <u>Diameter</u> | <u>Information</u> |
|---------------------------|----------|----------|----------|-----------------|----------------------------------|
| ELECTRICITY | 1.085 | 182 | 0 | | Prever Interruptor diferencial |
| COLD WATER | 1.045 | 80 | 0 | 1/2" | Prever llave de corte en la toma |

